CLAIMS

1. A recording apparatus for recording an image on a recording medium on the basis of image data supplied from an image supply device, characterized by
5   comprising:

setting means for setting an overlay recording mode of a plurality of images depending on whether or not the image supply device sets a recording condition corresponding to a plurality of conditions required to
10   overlay and record a plurality of images supplied from the image supply device; and

control means for, in a case where said setting means sets the overlay recording mode of the plurality of images, controlling to overlay and record the
15   plurality of images supplied from the image supply device.

2. The apparatus according to claim 1, characterized in that:
20   in a case where a recording start command supplied from the image supply device includes a layout command and a plurality of image formats, said setting means sets the overlay recording mode of a plurality of images included in the recording start command.
25

3. The apparatus according to claim 1, characterized in that the plurality of conditions include conditions

that a plurality of image formats are included, and the

plurality of images include at least one JPEG image,

and a predetermined number of PNG images.

5   4. The apparatus according to claim 3, characterized

in that the plurality of conditions further include the

number of records and/or the number of images to be

recorded on a single recording medium as a condition.

10   5. The apparatus according to claim 3, characterized

in that said control means overlays the plurality of

images supplied from the image supply device in an

order in which the images are received.

15   6. The apparatus according to claim 1, characterized

in that the plurality of image formats include at least

one of an image format that designates an image which

can be seen through, an image format that designates an

image file stored at a specific storage location, an

20   image format that designates an image file with a

specific file name, an image format that designates an

image file with specific tag information, and an image

format that designates image files in a specific order.

25   7. An image supply device for supplying image data to

an image output device, characterized by comprising:

command issuance means for issuing an image

output command set with an overlay recording mode of a
plurality of images depending on whether or not the
image output device has a plurality of functions
corresponding to a plurality of conditions required to
5   overlay and recording the plurality of images; and
        means for supplying image data, which is
requested from the image output device in response to
the image output command issued by said command
issuance means, to the image output device.
10

8. An image supply device for supplying image data to
an image output device, characterized by comprising:
        first acquisition means for acquiring format
information of image files that can be handled by the
15 image output device;
        second acquisition means for, in a case where the
format information acquired by said first acquisition
means includes predetermined format information,
acquiring a layout function supported by the image
20 output device;
        setting means for, in a case where the layout
function acquired by said second acquisition means
satisfies a predetermined condition, setting a
plurality of image data and a layout function to be
25 supplied to the image output device;
        command issuance means for issuing an image
output command to the image output device on the basis

of the plurality of image data and the layout function
set by said setting means; and

      means for supplying image data, which is
requested from the image output device in response to
5   the image output command issued by said command
issuance means, to the image output device.

9.   The device according to claim 8, characterized in
that the predetermined format information includes a
10   JPEG format and a PNG format.

10. The device according to claim 8, characterized in
that the predetermined condition of the layout function
includes a 1-up or N-up function.
15

11. A control method for a recording apparatus for
recording an image on a recording medium on the basis
of image data supplied from an image supply device,
characterized by comprising:
20   a setting step of setting an overlay recording
mode of a plurality of images depending on whether or
not the image supply device sets recording conditions
corresponding to a plurality of conditions required to
overlay and record a plurality of images supplied from
25   the image supply device; and
          a control step of controlling, in a case where
the overlay recording mode of the plurality of images

is set in said setting step, to overlay and record the
plurality of images supplied from the image supply
device.

5   12. The method according to claim 11, characterized in
that said setting step includes a step of setting, in a
case where a recording start command supplied from the
image supply device includes a layout command and a
plurality of image formats, the overlay recording mode
10 of a plurality of images included in the recording
start command.

13. The method according to claim 11, characterized in
that the plurality of conditions include conditions
15 that a plurality of image formats are included, and the
plurality of images include at least one JPEG image,
and a predetermined number of PNG images.

14. The method according to claim 13, characterized in
20 that the plurality of conditions further include the
number of records and/or the number of images to be
recorded on a single recording medium as a condition.

15. The method according to claim 13, characterized in
25 that said control step includes a step of overlaying
the plurality of images supplied from the image supply
device in an order in which the images are received.

16. A control method for an image supply device for
supplying image data to an image output device,
characterized by comprising:

5   a first acquisition step of acquiring format
information of image files that can be handled by the
image output device;

a second acquisition step of, in a case where the
format information acquired in said first acquisition

10   step includes predetermined format information,
acquiring a layout function supported by the image
output device;

a setting step of setting, in a case where the
layout function acquired in said second acquisition

15 step satisfies a predetermined condition, a plurality
of image data and a layout function to be supplied to
the image output device;

a command issuance step of issuing an image
output command to the image output device on the basis

20   of the plurality of image data and the layout function
set in said setting step; and

a step of supplying image data, which is
requested from the image output device in response to
the image output command issued in said command

25   issuance step, to the image output device.

17. The method according to claim 16, characterized in

that the predetermined format information includes a

JPEG format and a PNG format.

18.   The method according to claim 16, characterized in

5   that the predetermined condition of the layout function

includes a 1-up or N-up function.

19.   A program characterized by executing a control

method of claim 11.

10

20.   A program characterized by executing a control

method of claim 16.

21.   A recording apparatus for recording an image on a

15   recording medium on the basis of image data supplied

from an image supply device, characterized by

comprising:

reception means for receiving a recording command

with a hierarchical structure, which is transmitted

20   from the image supply device;

first determination means for determining whether

an upper layer of the recording command designates a

first recording mode that records a plurality of images

on a single recording medium;

25   second determination means for, in a case where

said first determination means determines that the

first recording mode is designated, determining a

second recording mode designated by a lower layer of

the upper layer; and

        control means for controlling to execute, in a

case where said second determination means cannot

5   determine the second recording mode, a recording

operation according to the first recording mode

determined by said first determination means, and to

execute, in a case where said second determination

means can determine the second recording mode, a

10 recording operation according to the second recording

mode determined by said second determination means.

22. The apparatus according to claim 21, characterized

in that the second recording mode is a mode for

15 determining positions of a plurality of images to be

recorded on the single recording medium in a recording

process.

23. The apparatus according to claim 21, characterized

20 in that the second recording mode is a mode for

overlaying the other image on one image of a plurality

of images to be recorded on the single recording medium

in a recording process.

25 24. The apparatus according to claim 21, characterized

in that:

        in a case where the second recording mode

includes a recording mode based on composition of a
background image, and an image to be overlaid on the
background image, said apparatus further comprising:

specifying means for specifying the background

5   image; and

variable magnification means for applying a
variable magnification process of the background image
specified by said specifying means in correspondence
with the size of the recording medium.

10

25.   The apparatus according to claim 24, characterized
in that said specifying means identifies based on a
storage location of an image file in the image supply
device whether the image file is designated as the

15   background image.

26.   The apparatus according to claim 24, characterized
in that said specifying means specifies based on a file
name of an image file in the image supply device that

20   an image in the image file is the background image.

27.   The apparatus according to claim 24, characterized
in that said specifying means specifies based on a file
type of an image file in the image supply device that

25   an image of the image file is the background image.

28.   The apparatus according to claim 24, characterized

in that said specifying means specifies based on tag
information of an image file in the image supply device
that an image of the image file is the background image.

5   29.   The apparatus according to claim 24, characterized
in that said specifying means specifies based on a
transfer order of image files transferred from the
image supply device that an image of the image file is
the background image.

10

30.   A recording system including an image supply
device and a recording apparatus, and recording an
image on a recording medium by the recording apparatus
on the basis of image data supplied from the image

15   supply device, characterized in that:
          the image supply device transmits a recording
command with a hierarchical structure to the recording
apparatus, and
          the recording apparatus comprising:

20   reception means for receiving a recording command
with a hierarchical structure, which was transmitted
from the image supply device;
          first determination means for determining whether
an upper layer of the recording command designates a

25   first recording mode that records a plurality of images
on a single recording medium;
          second determination means for, in a case where

- 83 -

said first determination means determines that the
first recording mode is designated, determining a
second recording mode designated by a lower layer of
the upper layer; and

5   control means for controlling to execute, in a
case where said second determination means cannot
determine the second recording mode, a recording
operation according to the first recording mode
determined by said first determination means, and to
10   execute, in a case where said second determination
means can determine the second recording mode, a
recording operation according to the second recording
mode determined by said second determination means.

15   31. The system according to claim 30, characterized in
that the second recording mode is a mode for
determining positions of the plurality of images to be
recorded on the single recording medium in a recording
process.

20

32. The system according to claim 30, characterized in
that the second recording mode is a mode for overlaying
the other image on one image of the plurality of images
to be recorded on the single recording medium in a
25   recording process.

33. A control method in a recording system for

recording an image on a recording medium by the
recording apparatus on the basis of image data supplied
from an image supply device, characterized by
comprising:

5   a transmission step of transmitting a recording
command with a hierarchical structure from the image
supply device to the recording apparatus;

        a first determination step of determining whether
an upper layer of the recording command transmitted in
10   the transmission step designates a first recording mode
that records a plurality of images on a single
recording medium;

        a second determination step of determining, in a
case where it is determined in said first determination
15   step that the first recording mode is designated, a
second recording mode designated by a lower layer of
the upper layer; and

        a step of executing, in a case where the second
recording mode cannot be determined in said second
20   determination step, a recording operation according to
the first recording mode determined in said first
determination step; and

        a step of executing, in a case where the second
recording mode can be determined in said second
25   determination step, a recording operation according to
the second recording mode determined in said second
determination step.

34. The method according to claim 33, characterized in that the second recording mode is a mode for determining positions of the plurality of images to be

5 recorded on the single recording medium in a recording process.

35. The method according to claim 33, characterized in that the second recording mode is a mode for overlaying

10 an image on one image of the plurality of images to be recorded on the single recording medium in a recording process.

36. A program for executing a control method in a

15 recording system for recording an image on a recording medium by the recording apparatus on the basis of image data supplied from an image supply device, characterized by comprising:

a transmission step module of transmitting a

20 recording command with a hierarchical structure from the image supply device to a recording apparatus;

a first determination step module of determining whether an upper layer of the recording command transmitted in said transmission step designates a

25 first recording mode that records a plurality of images on a single recording medium;

a second determination step module of determining,

in a case where it is determined in said first

determination step that the first recording mode is

designated, a second recording mode designated by a

lower layer of the upper layer; and

5   a step module of executing, in a case where the

second recording mode cannot be determined in said

second determination step, a recording operation

according to the first recording mode determined in

said first determination step; and

10   a step module of executing, in a case where the

second recording mode can be determined in said second

determination step, a recording operation according to

the second recording mode determined in said second

determination step.

15

37. A recording apparatus for recording an image on a

recording medium based on image data supplied from an

image supply device, characterized by comprising:

           reception means for receiving a layout condition

20   from the image supply device, wherein the layout

condition specifies a layout of recording a plurality

of items of image data on a recording medium, which are

supplied from the image supply device; and

           control means for controlling to record a

25   plurality of items of image data supplied from the

image supply device by overlapping or not overlapping

in accordance with the layout condition, based on

formats of the items of image data.

38. An apparatus according to claim 37, characterized
in that said control means controls to record an image
5   whose format designates an image to be seen through, by
overlapping with another image.

39. An apparatus according to claim 37, characterized
in that said control means controls to record an image
10   by overlapping with another image, in a case where a
type of the image is different from a type of another
image.

40. An apparatus according to claim 37, characterized
15   in that any one of the formats includes JPEG or other
than JPEG.

41. A recording apparatus for recording an image on a
recording medium based on image data supplied from an
20   image supply device, characterized by comprising:
reception means for receiving a layout command
for specifying a layout of recording a plurality of
images on a recording medium and designation data for
designating a plurality of images to be recorded, from
25   the image supply device; and
control means for controlling to record a
specific image by overlapping with another image, in a

case where images designated by the designation data
include the specific image.

42. An apparatus according to claim 41, characterized
5   in that the specific image is an image to be seen
through.

43. An apparatus according to claim 41, characterized
in that the specific image has a predetermined format
10   of image other than JPEG.

44. An apparatus according to claim 41, characterized
in that the specific image has a predetermined file
name or arranged in a predetermined holder.
15

45. An apparatus according to claim 41, characterized
by further comprising set means for setting an order of
overlapping images in accordance with an order of
designation of images among the images designated by
20   the designation data.

46. A recording method of recording an image on a
recording medium based on image data supplied from an
image supply device, characterized by comprising the
25   steps of:

receiving a layout condition from the image
supply device, wherein the layout condition specifies a

layout of recording a plurality of items of image data
on a recording medium, which are supplied from the
image supply device; and

controlling to record a plurality of items of
5   image data supplied from the image supply device by
overlapping or not overlapping in accordance with the
layout condition, based on formats of the items of
image data.

10   47. A recording method of recording an image on a
recording medium based on image data supplied from an
image supply device, characterized by comprising the
steps of:

receiving a layout command for specifying a
15   layout of recording a plurality of images on a
recording medium and designation data for designating a
plurality of images to be recorded, from the image
supply device; and

controlling to record a specific image by
20   overlapping with another image, in a case where images
designated by the designation data include the specific
image.

48. A computer readable recording medium characterized
25   by storing a program of implementing a recording method
according to claim 46.

49. A computer readable recording medium characterized
by storing a program of implementing a recording method
according to claim 47.

5   50. A program characterized by implementing a
recording method according to claim 46.

51. A program characterized by implementing a
recording method according to claim 47.

10